Chapter 15

Chapter 15 The Linker Utility (LINK)

Functions of the Linker 15–1
Calling and Terminating the Linker 15–2
Command-Line Syntax 15–3
Linker Input 15–6
    Input Object Modules 15–6
    Input Library Modules 15–6
Linker Output 15–11
    Output Load Module 15–11
    Output Load Map 15–13
How the Linker Structures the Load Module 15–15
    Assigning Absolute Addresses 15–15
    Creating an Absolute Section 15–15
    Allocating Memory for Program Sections 15–15
Communicating Between Modules (Global Symbols) 15–20
LINK Option Descriptions 15–21
LINK Option Summary 15–42
DCL Equivalents of LINK Utility Operations 15–45

Figures

15–1 Library Searches 15–8
15–2 Sample Load Map 15–13
15–3 Global Data Section with CON Attribute 15–24
15–4 Global Data Section with OVR Attribute 15–24
15–5 Virtual and Physical Address Space with One Virtual Region 15–35
15–6 Virtual and Physical Address Space with Two Overlay Regions 15–37
15–7 Extended-Memory Partitions that Contain Sharing Segments 15–38

Tables

15–1 Linker Prompting Sequence 15–4
15–2 Absolute Block Parameters 15–11
15–3 PSECT Attributes 15–16
15–4 Section Attributes 15–18
15–5 PSECT Order 15–19
15–6 Linker Options 15–42
15–7 DCL Equivalents of LINK Utility Operations 15–45

LINK