

# System Support Addendum

PRODUCT NAME: VAX BASIC, Version 3.3

SSA 25.36.19-A

## HARDWARE REQUIREMENTS

### Processor Support

VAX: VAX 6210, VAX 6220, VAX 6230, VAX 6240,  
VAX 8200, VAX 8250, VAX 8300, VAX 8350,  
VAX 8500, VAX 8530, VAX 8550, VAX 8600,  
VAX 8650, VAX 8700, VAX 8800, VAX 8810,  
VAX 8820, VAX 8830, VAX 8840, VAX 8974,  
VAX 8978

VAX-11/725, VAX-11/730, VAX-11/750, VAX-11/780,  
VAX-11/785, VAX-11/782

Note: VMS installation needs to be tailored to support  
this product on VAX-11/725.

MicroVAX: MicroVAX I, MicroVAX II, MicroVAX 2000,  
MicroVAX 3500, MicroVAX 3600

VAXstation: VAXstation I, VAXstation II, VAXstation  
2000, VAXstation 3200, VAXstation 3500,  
VAXstation 8000

VAXserver: VAXserver 3500, 3600, 3602

### Block Space Requirements (Block Cluster Size = 1):

Disk space required during installation: 1600 Blocks  
(819.2K bytes)

Disk space required for use (permanent): 1100 Blocks  
(563.2K bytes)

These block counts refer to the disk space required on  
the system disk. The sizes are approximate; actual sizes  
may vary depending on the user's system environment,  
configuration and software options.

## OPTIONAL HARDWARE

Floating point intensive applications should be run on  
configurations with the appropriate hardware support for  
the floating point data types being used. Consult the  
base operating system SPD for the appropriate floating  
point accelerator or other floating point hardware appro-  
priate for your configuration.

## CLUSTER ENVIRONMENT

This layered product is fully supported when installed on  
any valid and licensed VAXcluster \* configuration  
without restrictions. The HARDWARE REQUIREMENTS

sections of this product's Software Product Description  
and System Support Addendum detail any special  
hardware required by this product.

\* V5.x VAXcluster configurations are fully described  
in the VAXcluster Software Product Description  
(29.78.xx) and include CI, Ethernet and Mixed  
Interconnect configurations.

## SOFTWARE REQUIREMENTS

### Operating System:

VMS Operating System V5.0

### Layered Products:

VMS Workstation Software V4.0

### VMS Tailoring

For VMS V5.x systems, the following VMS classes are  
required for full functionality of this layered product:

- Required Save Set
- Programming Support

## OPTIONAL SOFTWARE

To use %INCLUDE %FROM %CDD:

VAX Common Data Dictionary (CDD) V3.4

To use the %REPORT %DEPENDENCY directive and  
the /DEPENDENCY\_DATA qualifier:

VAX Common Data Dictionary/Plus (CDD/Plus) V4.0

To use the /DIAGNOSTICS qualifier:

VAX Language-Sensitive Editor V2.2

To use graphics statements:

VAX GKS Development or Run-time License V3.1

To use the /ANALYSIS\_DATA qualifier:

VAX Source Code Analyzer (SCA) V1.2

## GROWTH CONSIDERATIONS

The minimum hardware requirements for any future  
version of this product may be different than the mini-  
mum hardware requirements for the current version.

digital  
software

July 1988  
AE-LT32B-TE

VAX BASIC, Version 3.3

SSA 25.36.19-A

**DISTRIBUTION MEDIA**

Disk: RX50 Floppy Diskette, RX01 Floppy Diskette

Tape: 9-track 1600 BPI Magtape (PE), TK50 Streaming  
Tape, TU58 DECtape II Cartridge

**ORDERING INFORMATION**

Software Licenses: QL-095A\*-\*\*

Software Media: QA-095A\*-\*\*

Software Documentation: QA-095AA-GZ  
Software Product Services: QT-095A\*-\*\*

\* Denotes variant fields. For additional information on available licenses, services and media, refer to the appropriate price book.

The above information is valid at time of release. Please contact your local DIGITAL office for the most up-to-date information.